

ROTOPLAT 508 DW - DW/C

SEMI-AUTOMATIC STRETCH WRAPPER

Stretch wrapping turntable dedicated to doors, windows, and other finished and semi-finished products in this manufacturing industry available with idle rollers conveyor and manual product lock system.

- Also available with idler roller conveyor and device for manual product fixing.



*Rotoplat 508 DW-C shown

Performance features:



R-CONNECT READY

Developed to provide usage and performance data via the cloud. Utilization drastically reduces downtime by giving you informational transparency, allowing you to connect with your machines remotely to investigate alarms, adjust parameters, &

COLOR TOUCH SCREEN

The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the MULTILEVEL CONTROL function.




PDS CARRIAGE

PDS Carriage with dual pre-stretch rollers controlled via the control panel. Pre-stretch system stretch ratio adjustable from panel board up to 250%.



TURNTABLE DW

Manual product lock system.



TURNTABLE DW/C

Idle rollers conveyor and manual product lock system.



Rotoplat DW-DWC Specifications

Performance Criteria

Production Speed:

Up to 40 LPH

Turntable Speed:

5 – 12 RPM

Turntable Drive:

1 HP VAC

Load Handling System

Turntable Size:

65" Diameter

Maximum Load Height:

110"

Maximum Load Weight:

4400 lbs.

Film Delivery System

- Standard Pre-stretch: Variable 0 – 250%
- Containment Force: Multi-Level Variable
- Film Carriage Motor: ½ HP VAC
- Height Sensing: Automatic via photocell
- Film Threading: Patented S-Pattern
- Corner Compensation: Load Cell

Safety Features

- Anti-fall device on carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

Utilities

Voltage:

115V, 20 amps, 60 Hz, 1 PH

Warranty:

5 Years