

tesa® 4287

Tensilised strapping tape

PRODUCT INFORMATION

Product Description

tesa® 4287 is a tensilised polypropylene strapping tape with a natural rubber adhesive system.

tesa® 4287 exhibits good tensile strength with low elongation at the same time. The applied product is highly heat- and cold resistant.

Main Application

Palletising, belting of electronic components, bundling and closure of shipping cartons.

Technical Data

- Backing material
- Total thickness
- Type of adhesive
- MOPP 79 µm

natural rubber

- Adhesion to steel Elongation at break
 - Tensile strength
- 4 N/cm 35 %
- 180 N/cm

Properties

Residue free removal

yes

No discolouration

yes

For latest information on this product please visit http://l.tesa.com/?ip=04287

Page 1 of 1 / As of 02/02/14

Quickbornstraße 24 20253 Hamburg Germany Phone: +49 (40) 4909 101

http://www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Phone: +1 (704) 554 0707 Phone: +65 (68) 612 026

tesa tape Asia Pacific Pte. Ltd.

164 Gul Circle, Singapore 629621

Fax: +1 (704) 553 5634 Fax: +65 (68) 614 790 http://www.tesatape.com http://www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.